



6-Port 1000M AI PoE Switch

AI606G



Product Introduction:

AI606G, a 6-Port Gigabit AI PoE switch, the product has 4 working modes, AI VLAN mode, AI Extend mode, AI PoE mode, AI QoS mode; By default, all ports communicate freely;

Enable AI VLAN mode, 1-4 ports are isolated from each other, which can effectively suppress network storms and improve network performance;

Enable AI Extend mode, 1-4 ports effective transmission distance up to 250 meters, suitable for long-distance monitoring and power supply;

Enable AI PoE mode, the switch automatically detects the working condition of the PD device, and automatically restarts the device when it finds an abnormal device;

Enable AI QoS mode, video data is prioritized in case of device congestion, making video smoother.

Main features:

Port 6KV lightning protection

- All ports support 6KV lightning protection, support power supply over-temperature protection, over-voltage protection, surge current protection and other protection features.

Characteristics

- Non-blocking switching architecture, all ports support wire-speed forwarding.
- Support IEEE 802.3x full dual flow control and half dual backpressure flow control.
- Support port automatic flip(Auto MDI/MDIX).

AI smart button

- AI Extend: 1-4 ports support 250 meters long-distance power supply (recommended to use super five or more network cables).
- AI VLAN: Isolate ports 1-4 from each other, which can effectively suppress network storms and improve network performance.
- AI QoS: Prioritize the identified video data to make video transmission smoother.
- AI PoE: Automatically detect the power receiving port, find the dead device, and restart the device.

PoE characteristic

- Compliant with the IEEE802.3af&at standard, the maximum PoE power of a single port is 30W.
- Support PoE short circuit protection, over current protection, over temperature protection, etc.
- Support AI PoE, restart dead device.

Ease of use

- Plug and play, no configuration required, easy to use.
- With zero-configuration features, power is automatically supplied to adaptive devices.

Product Specifications:

Network port	● 4 * 10/100/1000M RJ45 PoE ports (port 1~port4)
	● 2 * 10/100/1000M RJ45 ports (port 5~port 6)
Network standard	● IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
Performance	● Bandwidth: 12Gbps (no block)
	● Frame filtering and transmission rate: 8.9Mpps
	● MAC table size: 2K
	● Forwarding type: Storage and Forwarding
LED indicator	● 1 Power Indicator
	● 6 LINK/ACT indicator
	● 4 PoE indicator
POE pin	● 1/2(+), 3/6(-)
Power	● The maximum output power of a single port is 30W
	● The maximum power of the whole machine: 60W
Dimensions	● Size(LxWxH) 150mm*127mm*40mm
Environment	● Operating Temperature：0°~40°C
	● Operating Humidity：10%~90%，Non-condensing
Safty	● CE/ROHS/FCC

Caution:

1. In order to safety, please non-professionals don't open the casing of product;
2. Please be careful the risk of strong current and security protection when products carry power;
3. Please select the right power adaptor provide power for PoE switch, before using please confirm if is it accord with the requirement of PoE switch;
4. Please don't use PoE switch under the humid environment, avoiding water go into the product inside caused PoE switch breakdown;
5. Please start the power after the circuit connected;
6. Please don't plug-in and plug-out the connection cable when product is carrying on power;
7. Please don't use PoE switch under somewhere with more dust and EME;
8. Please don't put heavy thing on PoE switch, in order to having an accident;
9. According to the IEEE802.3AF/AT standard, Please use the Cat.5 or above, transmission distance 250 m;
10. Please don't exceed the maximum output power of PoE switch when it connect more than one PD device;
11. Suggestion that PoE switch use for indoor, if you want to use for outdoor, Please install waterproof box.