

HORED 丰润达®

10 Ports Gigabit Managed Industrial Switch

IS108GS-2F

Product brochure

Shenzhen Fengrun Technology Co., Ltd

Product Introduction

IS108GS-2F is a 10-port gigabit managed industrial Ethernet switch with 8 gigabit RJ45 ports and 2 gigabit optical ports, especially suitable for application scenarios which it is difficult to provide AC power and want to save the wiring costs. EMC Class 4 protection performance; corrugated high-strength aluminum profile shell, IP40 grade, low power consumption design, anti-vibration DIN-rail installation, operating temperature of -40°C-75°C, can work in harsh environments. IS108GS-2F can also support various network management functions: RUN-Ring (self-healing time <10ms), RSTP, VLAN, QoS, SNMPv1/v2c/v3, IEEE802.1X, SSH/SSL, port mirror, port aggregation, etc. The IS108GS-2F is a reliable solution for intelligent transportation, video surveillance and other harsh industrial environments by its rich redundancy, switching and security management features.



Highlights

Port 6KV lightning protection

- All ports support 6KV lightning protection, power short circuit protection, overvoltage protection and surge current protection features.

AI smart button

- AI Loop Protect: Using the RUN-Ring technology, when the main link of the network transmission fails, the system automatically switches to the backup link, and the fault recovery time can reach as fast as 10ms.
- AI VLAN: Isolating ports 1-8 from each other, so that can suppress network storms effectively and improve network performance.

Powerful application capabilities

- Support 802.1Q VLAN, MAC VLAN, IP VLAN, users can divide VLAN flexibly as needed.
- Support QoS, 8 port queues, support port priority, 802.1P priority, DSCP priority, support SP, WRR, SP+WRR, WFQ priority scheduling algorithm.
- Support ACL, support L2 (Layer 2) ~ L4 (Layer 4) packet filtering function, provide flexible and secure access control policy.
- Supports IGMP v1/v2/v3 Snooping and MLD v1/v2 Snooping to meet the requirements of multi-terminal HD video surveillance or video conferencing.
- It supports the fast leave mechanism and querier of Layer 2 multicast, and supports Layer 2 IPv4 static multicast and Layer 2 IPv6 static multicast.

Full security mechanism

- Completed security authentication mechanism: It supports IEEE 802.1x, Radius, Tacacs+, etc.
- The loop detection mechanism can ensure the stable operation of the network for a long time.
- High security features such as port isolation in VLAN, DHCP-Snooping and IP+MAC+port binding, etc., to further ensure user data security.
- Support multi protections like ARP, IP source and DoS.
- Support declining user access by the port numbers, IP address, and MAC address.

Diverse reliability protection

- Support STP (IEEE 802.1d), RSTP (IEEE 802.1w) and MSTP (IEEE 802.1s) protocols to eliminate Layer 2 loops and implement link backup.
- Supports loop protection, root bridge protection, TC protection, BPDU protection, and BPDU filtering.
- Supports relay alarm output functions such as power failure and port disconnection.
- EMC Class4 and anti-jamming capability.

Flexible and convenient management and maintenance

- Support various management methods such as Console, Telnet, and SSH.
- Support simple and efficient WEB management (HTTP, HTTPS, SSL V3)
- Support TFTP mode to upload and download files.
- Support SNMP V1/V2/V3
- Support Hored Apollo cloud platform, which can realize all-round remote operation and maintenance such as automatic device discovery, network topology management, and remote configuration management of devices.

Compliance

EMI: FCC CFR47 Part 15, EN55022/CISPR22, Class A

EMS:

IEC61000-4-2 (ESD): $\pm 8\text{kV}$ (contact), $\pm 15\text{kV}$ (air)

IEC61000-4-3 (RS): 10V/m (80MHz-2GHz)

IEC61000-4-4 (EFT): Power Port: $\pm 4\text{kV}$; Data Port: $\pm 2\text{kV}$

IEC61000-4-5 (Surge): Power Port: $\pm 2\text{kV/DM}$, $\pm 4\text{kV/CM}$; Data Port: $\pm 6\text{kV}$

IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz)

IEC60068-2-6 (Vibration)

IEC60068-2-27 (Shock)

IEC60068-2-32 (Free Fall)

Specifications

Hardware	
Network Interface	<ul style="list-style-type: none"> • 10/100/1000Mbps RJ45 ports x8 • 10/100/1000Mbps SFP ports x2 • Console ports x1
Network Protocol	<ul style="list-style-type: none"> • IEEE802.3、IEEE802.3i、IEEE802.3u、IEEE802.3ab、IEEE802.3z、IEEE802.3ad、IEEE802.3x、IEEE802.1p、IEEE802.1q、IEEE802.1w、IEEE802.1d、IEEE802.1s
Performance	<ul style="list-style-type: none"> • Bandwidth:20Gbps (Non-Block) • Throughput : 14.9Mpps • MAC table : 8K • Port cache : 4.1Mb • Forwarding model: Store and forward
LED Indicator	<ul style="list-style-type: none"> • Power Indicator : P1,P2 • System Indicator : SYS • Alarm Indicator : ALM • SFP Port Indicator : Link&Act F1~F2 • RJ45 Port Indicator : Link&Act 1~8
Power Supply	<ul style="list-style-type: none"> • Input voltage : 12-56V DC • Input port : Pluggable 5 pin terminals block, 5.08mm pitch (support dual DC power source backup, built-in overcurrent protection, support anti-reverse connection)
Physical Parameter	<ul style="list-style-type: none"> • Casing : Corrugated high-strength metal housing, IP40 • Installation : DIN-Rail • Dimension (LxWxH) : 163mm×110mm×46.5mm
Environmental Condition	<ul style="list-style-type: none"> • Operating Temperature : -40~75°C • Storage Temperature : -40~85°C • Operating Humidity : 5%~95% RH (non-condensing) • Storage Humidity : 0%~95% RH (non-condensing)
Certification	<ul style="list-style-type: none"> • CE/ROHS/FCC

Software	
Protocol	IEEE 802.3: Ethernet Media Access Control (MAC) protocol IEEE 802.3i: 10BASE-T Ethernet IEEE 802.3u: 100BASE-TX fast Ethernet IEEE 802.3ab: 1000BASE-T gigabit Ethernet IEEE 802.3z: 1000BASE-X gigabit Ethernet(fiber) IEEE 802.3ad: Comply link aggregation standard IEEE 802.3x: Flow control IEEE 802.1p: About the traffic priority of the second layer of Qos / Cos protocol (multicast filtering) IEEE 802.1q: VLAN Bridge operation IEEE 802.1d: STP spanning tree IEEE 802.1s: MSTP spanning tree IEEE 802.1w: RSTP spanning tree IEEE 802.3af IEEE 802.3at
AI Button	AI Loop Protect AI VLAN
DHCP	DHCP Snooping
VLAN	4K VLAN 802.1Q VLAN、MAC VLAN ,IP VLAN Voice VLAN
MAC Table	IEEE 802.1d Support MAC address automatic learning and aging Support static, dynamic, filtering address table
Security	Password protection Decline user access by port number, IP address and MAC address HTTPS、SSL V3、TLS V1、SSH V1/V2 Support IP-MAC-PORT ternary binding ARP Protection、IP source Protection、DoS Protection Support DHCP Snooping and DHCP attack protection Support 802.1X authentication, AAA Support port security, port isolation Support CPU protection

Software	
ACL	Support L2 (Layer 2) ~ L4 (Layer 4) packet filtering function Support port mirroring, port redirection, flow rate limit, QoS remarking
QoS	Support 8 port queues Support port priority, 802.1P priority, DSCP priority Support SP, RR, WRR, priority scheduling algorithm
Spanning Tree	Support STP(IEEE 802.1d) , RSTP(IEEE 802.1w) and MSTP(IEEE 802.1s) Support loop protection, root bridge protection, TC protection, BPDU protection, BPDU filtering
Multicast	Support IGMP v1/v2 Snooping Support multicast VLAN Supports multicast filtering, packet statistics, and unknown multicast discards
Storm Suppression	Multicast suppression Broadcast suppression Unknown unicast suppression
Link Aggregation	Static aggregation Dynamic aggregation Support IP, MAC, and hybrid load balancing modes Up to 32 aggregation groups
IPv6	IPv6 Ping、 IPv6 Tracert、 IPv6 Telnet IPv6 SSH 、 IPv6 SSL
Management and Maintenance	WEB management (HTTP、 HTTPS、 SSL V3) CLI (Telnet, SSH V1/V2, Local serial port) SNMP V1/V2/V3 LLDP、 RMON ARP protection, IP source protection, DoS protection CPU monitoring, memory monitoring System log, grading warning Support Ping, Tracert detection, cable detection